

# DH-HAC-HDW1249X-A-PRO

2MP WizColor HDCVI Fixed-focal Eyeball Camera



## Series Overview

The Lite Series is a great choice for consumers looking for high quality monitoring products at a reasonable price. Its low cost and high performance make it ideal for residential areas and SMB solutions. This series is equipped with a wide range of technologies, such as full-color and starlight, providing various solutions for different scenarios.

## Functions

### WizColor Technology

Dahua WizColor Technology seamlessly combines with the powerful AI-ISP and large aperture in cameras. This unique integration enables cameras to effortlessly capture high-quality images with vibrant colors during nighttime scenarios, ensuring fine details are preserved and minimizing motion blur. Unlike traditional self-illuminating cameras, Dahua WizColor Technology maximizes the utilization of weak light sources, such as moonlight and city lights reflected in the sky, delivering captivating full-color images of the entire scene. It also ensures that monitoring distances are not compromised at night due to limited illumination ranges, facilitating full-color image capture even over long distances.

### AI-ISP

With AI ISP technology, the camera is able to easily adapt to scenes, producing high quality images that reveal the fine details of targets.

### Full-color

With its advanced image processing algorithm and capability to absorb large quantities of light, the camera provides 24/7 color monitoring that collects clear and highly detailed information, significantly increasing the reliability of the human and vehicle images that are collected as evidence for intelligent analysis.

- 24/7 color imaging, Max. 30 fps@1080p
- AI-ISP.
- Distortion Correction.
- Smart Light+.
- 50 m illumination distance
- Super Adapt, 3D NR
- Built-in Dual Mic
- Quick-to-install eyeball saves installation time.
- 3.6 mm fixed lens (2.8 mm optional)
- CVI/CVBS/AHD/TVI switchable
- IP67, 12 VDC



### Distortion Correction

With advanced distortion correction algorithm, Dahua Distortion Correction corrects the image distortion in both horizontal and vertical directions to be consistent with the actual situation.

### Smart Light+

Equipped with advanced LEDs and beam processing technology, the camera effectively reduces interference of stray light, ensuring concentrated illumination within the lens's field of view. This allows the camera to easily produce clear images that reveal the fine details of targets even in low light conditions.

### Built-in Dual Mic

Equipped with Dual Mic audio processing technology combined with intelligent noise reduction algorithms, HDCVI cameras effectively suppress environmental background noise and enhance audio clarity and pickup distance, ensuring the authenticity and reliability of the captured audio information. This technology protects the integrity of audio evidence in video surveillance, making it particularly suitable for scenes that require both audio and videos for verification.

### Easy Installation

HDCVI eyeball comes with a quick-to-install pedestal, which makes it easier to install than conventional eyeballs and reduces cost on time and labor.

### Protection

**IP67:** The camera passed a series of rigorous dust and immersion tests. Its enclosure is both dust-proof and waterproof, and can function normally while being immersed in 1 m deep water for up to 30 minutes. **Wide voltage:** The camera has  $\pm 30\%$  input voltage tolerance (for some power supplies) and a wide voltage range, making it suitable for a variety of outdoor scenarios.

Protection

IP67: The camera passed a series of rigorous dust and immersion tests. Its enclosure is both dust-proof and waterproof, and can function normally while being immersed in 1 m deep water for up to 30 minutes.

Wide voltage: The camera has  $\pm 30\%$  input voltage tolerance (for some power supplies) and a wide voltage range, making it suitable for a variety of outdoor scenarios.

Technical Specification

|                            |                                                           |
|----------------------------|-----------------------------------------------------------|
| Camera                     |                                                           |
| Image Sensor               | 2 MP CMOS                                                 |
| Max. Resolution            | 1920 (H) × 1080 (V)                                       |
| Scanning System            | Progressive                                               |
| Electronic Shutter Speed   | PAL: 1/25 s–1/100,000 s<br>NTSC: 1/30 s–1/100,000 s       |
| Min. Illumination          | 0.0001 lux@F1.0 (Color, 30 IRE)<br>0 lux (Illuminator on) |
| S/N Ratio                  | >65 dB                                                    |
| Illumination Distance      | 50 m (164.04 ft)                                          |
| Illuminator On/Off Control | Auto                                                      |
| Illuminator Number         | 4 (Warm light)                                            |
| Angle Adjustment           | Pan: 0°–360°<br>Tilt: 0°–78°<br>Rotation: 0°–360°         |

|                      |                                                                              |
|----------------------|------------------------------------------------------------------------------|
| Lens                 |                                                                              |
| Lens Type            | Fixed-focal                                                                  |
| Lens Mount           | M12                                                                          |
| Focal Length         | 2.8 mm; 3.6 mm                                                               |
| Max. Aperture        | F1.0                                                                         |
| Field of View        | 2.8 mm: H: 101°; V: 53.4°; D: 119.5°<br>3.6 mm: H: 81.5°; V: 44.3°; D: 95.7° |
| Iris Control         | Fixed                                                                        |
| Close Focus Distance | 2.8 mm: 1.1 m (3.61 ft)<br>3.6 mm: 1.7 m (5.58 ft)                           |

|               |                                                                                                                                                                                                                                                                                                                                                                                 |                        |                       |                       |                      |
|---------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------|-----------------------|-----------------------|----------------------|
| DORI Distance | Lens                                                                                                                                                                                                                                                                                                                                                                            | Detect                 | Observe               | Recognize             | Identify             |
|               | 2.8 mm                                                                                                                                                                                                                                                                                                                                                                          | 47.1 m<br>( 154.53 ft) | 18.9 m<br>( 62.01 ft) | 9.4 m<br>( 30.84 ft)  | 4.7 m<br>( 15.42 ft) |
|               | 3.6 mm                                                                                                                                                                                                                                                                                                                                                                          | 55.7 m<br>( 182.74 ft) | 22.3 m<br>( 73.16 ft) | 11.1 m<br>( 36.42 ft) | 5.6 m<br>( 18.37 ft) |
|               | *DORI (Detect, Observe, Recognize, Identify) is a standard system (EN-62676-4) for defining the ability of a person viewing the video to distinguish persons or objects within a covered area. The numbers in this table do not reflect intelligent function distances. For intelligent function distances, refer to installation and commissioning manual/project design tool. |                        |                       |                       |                      |

Video

|                  |                                                           |
|------------------|-----------------------------------------------------------|
| Video Frame Rate | CVI:<br>PAL: 1080p@25 fps;<br>NTSC: 1080p@30 fps;<br>AHD: |
|------------------|-----------------------------------------------------------|

|                   |                                                                                                                                     |
|-------------------|-------------------------------------------------------------------------------------------------------------------------------------|
| Video Frame Rate  | PAL: 1080p@25 fps;<br>NTSC: 1080p@30 fps;<br>TVI:<br>PAL: 1080p@25 fps;<br>NTSC: 1080p@30 fps;<br>CVBS:<br>PAL: 960H;<br>NTSC: 960H |
| Resolution        | 1080p (1920 × 1080); 960H (960 × 576/960 × 480)                                                                                     |
| Day/Night         | Color                                                                                                                               |
| BLC               | BLC; HLC; WDR                                                                                                                       |
| WDR               | 130 dB                                                                                                                              |
| White Balance     | Auto                                                                                                                                |
| Gain Control      | Auto                                                                                                                                |
| Noise Reduction   | 3D NR                                                                                                                               |
| Motion Detection  | Yes (It needs to be controlled through the XVR)                                                                                     |
| Illumination Mode | Smart Light                                                                                                                         |
| Mirror            | Yes (It needs to be controlled through the XVR)                                                                                     |

|                |                                                    |
|----------------|----------------------------------------------------|
| Certification  |                                                    |
| Certifications | CE-LVD: EN 62368-1;<br>CE-EMC: EN 55032; EN 55035; |

|                  |                        |
|------------------|------------------------|
| Audio            |                        |
| Built-in Mic     | Yes, built-in dual Mic |
| Camera Audio     | CVI                    |
| Pick-up Distance | 12 m (39.37 ft)        |

|              |                                                                       |
|--------------|-----------------------------------------------------------------------|
| Port         |                                                                       |
| Video Output | Video output choices of CVI/TVI/AHD/CVBS by one BNC port (DIP Switch) |

|                   |                            |
|-------------------|----------------------------|
| Power             |                            |
| Power Supply      | 12 VDC ( $\pm 30\%$ )      |
| Power Consumption | Max 5.6 W (12 VDC, LED on) |

|                       |                                      |
|-----------------------|--------------------------------------|
| Environment           |                                      |
| Operating Temperature | −40 °C to +60 °C (−40 °F to +140 °F) |
| Operating Humidity    | <95% (RH), non-condensing            |
| Storage Temperature   | −40 °C to +60 °C (−40 °F to +140 °F) |
| Storage Humidity      | <95% (RH), non-condensing            |
| Protection            | IP67                                 |
| Anti-corrosion Level  | Basic Protection                     |

|                    |                                                |
|--------------------|------------------------------------------------|
| Structure          |                                                |
| Casing Material    | Dome (metal + plastic) + plastic enclosure     |
| Product Dimensions | Φ109.9 mm × 102.2 mm (Φ4.33" × 4.02")          |
| Net Weight         | 0.33 kg (0.73 lb)                              |
| Gross Weight       | 0.45 kg (0.99 lb)                              |
| Installation       | Wall mount; ceiling mount; vertical pole mount |

Ordering Information

| Type                   | Model                  | Description                                        |
|------------------------|------------------------|----------------------------------------------------|
| HDCVI CAMERA           | DH-HAC-HDW1249XN-A-PRO | 2MP WizColor HDCVI Fixed-focal Eyeball Camera,NTSC |
|                        | DH-HAC-HDW1249XP-A-PRO | 2MP WizColor HDCVI Fixed-focal Eyeball Camera,PAL  |
| Accessories (Optional) | DH-PFB220C             | Ceiling Mount Bracket                              |
|                        | DH-PFA109              | Mount Adapter                                      |
|                        | DH-PFA151              | Corner Mount Bracket                               |
|                        | DH-PFB305W             | Wall Mount Bracket                                 |
|                        | DH-PFA150              | Pole Mount Bracket                                 |
|                        | DH-PFB2203W            | Wall Mount Bracket                                 |
|                        | DH-PFA156              | Pole Mount Bracket                                 |
|                        | DH-PFA13G              | Junction Box                                       |
|                        | DH-PFM800-E            | 1 Channel Passive HDCVI Balun                      |
|                        | DH-PFM321-EN           | DC12V1A power adapter                              |
|                        | DH-PFM320D-EN          | DC12V2A power adapter                              |
|                        | PFM904                 | Integrated Mount Tester                            |

Accessories

Optional:



DH-PFA109  
Mount Adapter



DH-PFA13G  
Junction Box



DH-PFA150  
Pole Mount Bracket



DH-PFA151  
Corner Mount Bracket



DH-PFA156  
Pole Mount Bracket



DH-PFB2203W  
Wall Mount Bracket



DH-PFB220C  
Ceiling Mount Bracket



DH-PFB305W  
Wall Mount Bracket



DH-PFM320D-EN  
DC12V2A power adapter




DH-PFM321-EN  
DC12V1A power adapter



DH-PFM800-E  
1 Channel Passive HDCVI Balun



PFM904  
Integrated Mount Tester



Dimensions (mm[inch])

