

# 60 Series Cabinet

## 60KG Loading Capacity Wall Mount Cabinets

### Features

- Various sizes and parts are available according to different application demand
- Completely welded structure, firm and reliable
- Cable in/out access at the top, bottom and rear for convenient cabling on site
- Embedded side panel, tool free in assembling and dismantling, lock is optional
- Front door can be dismantled and change from right to left quickly without tools, opening angle 180°, convenient for equipments installation and maintenance
- Providing several copper grounding stud castor or adjustable feet is optional for fix to the ground
- Maximum static loading is 60kgs
- Surface treatment procedure is degreasing→pickling-->anti-rust and phosphorization→water cleaning-->powder coating, RoHS compliant



### Application

Specially designed for internet servers, provides excellent and stable work environment for equipments inside the cabinet, used in data centers of bank, financial, telecom,government, education and security departments.

### Standards

Comply with EIA-310-E, IEC297-2, DIN41491 PART1, DIN41494 PART7, GB/T3047.2-92 standard, compatible with ETSI standard.

### 60 Series Door Style



### Ordering Information

| Model     | Capacity (U) | Width (mm) | Depth (mm) | Height (mm) | Packing Dimension (mm) |       |        | Volume (CBM) |
|-----------|--------------|------------|------------|-------------|------------------------|-------|--------|--------------|
|           |              |            |            |             | Width                  | Depth | Height |              |
| 6U64P060  | 6            | 600        | 450        | 370         | 640                    | 490   | 140    | 0.04         |
| 6U66P060  | 6            | 600        | 600        | 370         | 640                    | 640   | 220    | 0.09         |
| 9U64P060  | 9            | 600        | 450        | 503         | 640                    | 490   | 220    | 0.07         |
| 9U66P060  | 9            | 600        | 600        | 503         | 640                    | 640   | 220    | 0.09         |
| 12U64P060 | 12           | 600        | 450        | 637         | 675                    | 590   | 220    | 0.09         |
| 12U66P060 | 12           | 600        | 600        | 637         | 675                    | 640   | 220    | 0.10         |
| 15U64P060 | 15           | 600        | 450        | 770         | 810                    | 590   | 220    | 0.11         |
| 15U66P060 | 15           | 600        | 600        | 770         | 810                    | 640   | 220    | 0.11         |
| 18U64P060 | 18           | 600        | 450        | 903         | 940                    | 590   | 220    | 0.12         |
| 18U66P060 | 18           | 600        | 600        | 903         | 940                    | 640   | 220    | 0.13         |